

## UPLANDS HOMEOWNERS ASPHALT SHINGLE SELECTION GUIDE

Rev Jan 2024

APPROVED MANUFACTURERS Luxury Shingles	DESCRIPTION	kg/square	lbs/square	Warranty	UL790 Class A Fire Resistance	UL Certified ASTM D3462 Tear Resistance & Physical Properties	UL Certified ASTM D3018 Type 1 Uplift	UL Certified D3161 Wind Resistance Type F (110mph)	UL Certified ASTM D7158 Uplift Class G or H	Conforms CSA A123.5 Shingle Construction	Conform ICC-ES ESR 1389 & ESR 3537 Quality Control	Impact Resistance UL Certified UL2218 (steel balls) Class 3 or 4	bundles/square	shingles/square
Certainteed Presidential Shake TL	Three piece laminated fibreglass reinforced asphalt construction, look of cedar, rustic look, very heavy weight	218	480	50	YES	YES	YES	YES	H	YES	YES	4	6	90
Certainteed Presidential Shake	Two piece laminated fibreglass reinforced asphalt construction, rustic	160	355	50	YES	YES	YES	YES	H	YES	YES	4	5	90
Certainteed Grand Manor Slate	Two piece laminated fibreglass reinforced asphalt construction, appearance of natural slate	190	415	50	YES	YES	YES	YES	H	YES	YES	4	4	50
Certainteed Carriage House Shake	Two piece laminated fibreglass reinforced asphalt construction, unique chamfered cut for scalloped appearance	160	355	50	YES	YES	YES	YES	H	YES	YES	4	5	50
Certainteed Landmark TL Shake	Three piece laminated fibreglass reinforced asphalt construction, rustic appearance of hand split wood shakes	140	305	50	YES	YES	YES	YES	H	YES	YES	4	4	64
Malarkey Windsor Scotchgard Shake	NEX Polymer modified rubberized asphalt, environmentally friendly due to recycled rubber and plastics	160	350	50	YES	YES	YES	YES	H	YES	YES	4	5	65
Armourshake IKO Shake	Two piece laminated fibreglass reinforced asphalt construction, heavy weight	165	360	50	YES	YES	YES	YES	H	YES	YES	4	5	70